



## Select Hinged Door

### The Select Range

The Carinya Select Hinged Door is a premium product designed for those seeking superior functionality and style as a grand entry to their home.

Consisting of a modern designer look, the Carinya Hinged Door extrusions are a consistent 85mm wide face on both the stiles and rails, combined with a 40mm thick panel. This allows a balanced visual face and allows a vast array of hardware lock options. Combined with optional spigots, these door panels are superior in strength and performance.

✦ A 92mm frame is available for typical open out configurations. This also allows flexibility in design and budget.

✦ The Carinya attention to detail includes concealed flush bolt brackets, reducing visible fixings, as well as custom extrusion design allowing for clean interaction with door hardware.

The entire Carinya Collection has been fully tested to meet or exceed Australian Standards AS2047, AS1170, AS1191 and AS3959.



Carinya 92mm Hinged Door Sill Detail



Exclusive Killara furniture with 4 point locking and snib release

## STREAMLINED HARDWARE

The Carinya Select Hinged Door has been designed with hardware from the start, not as an after thought. All locks and flush bolts blend seamlessly with the custom extrusion for a professional finish.

The Carinya Select Hinged Door sashes feature an optional commercial door spigot, allowing a strong and robust panel for enduring use, free of twist and movement.

Standard lock hardware options include Alspec's custom Australian made Killara Furniture, combined with Lockwood's proven Optimum mortice lock. Fitting snug within the stile and allowing an extended 40mm backset, this lock removes the common issue of minimal key distance to the jamb.

Custom flush bolt guides have been designed to remove visible fixings from the extrusion faces, allowing a tighter seal saving potential energy costs while giving a professional, uninterrupted clean visible surface.

Killara Xtra Furniture allows for an internal snib option with lock indicator and four point locking for all configurations.

### Applications

- New residential construction.
- Window replacement and renovation.
- Low-rise Multi-Unit Developments

### Specifications

- Maximum Panel Height: 2400mm
- Maximum Panel Width: 900mm
- Maximum Single Glazed Thickness: 10.5mm
- Maximum Double Glazed Thickness: 24mm
- Maximum Panel Weight: 50kg
- 92mm Frame

### Configurations

Your Carinya Dealer can offer the typical standard configurations below, as well as custom options to suit your requirements:

